



REPOSITIONABLE INTERIOR DECAL INSTALLATION

PLEASE READ ALL OF THE INSTRUCTIONS BEFORE YOU BEGIN

These are recommended instructions only. We are not responsible for the end result.

Precautions before you begin:

- **DO NOT** store your decal in direct sunlight before application.
- It is best to install in temps. between 50° - 80° F and OUT of direct sunlight.
- Decals are best installed on a flat/smooth surface.

If being installed on a vehicle:

- For longer/better adhesion be sure there is no *Rain-X*, *Wax* or de-fogger on the surface.
- **DO NOT** wash application area for 3 days after application.
- **DO NOT** use ice scrapers on decal - it could damage it.

Basic Dry Application Instructions for a Small/Medium Decal:

1. Clean the application surface. To get the best possible result, you MUST remove all traces of dirt, grease, glues, etc. from the application surface. ***DO NOT use an AMMONIA based cleaner** (No Windex, etc.) - this will cause bubbling later! Soapy water in most cases is just fine. Be sure surface is dry before application.
2. Either measure or eyeball where you want to place the decal. **Please note: These are an adhesive based repositionable decal and can be removed and re-applied if desired. Take care to not touch the adhesive side since it will have an effect on how well it sticks. The removable backing is re-useable and can be used to store the decal if removed from the glass. Remember the decal is applied to the inside of the glass and the lettering will appear reversed from the inside of the vehicle.*
3. Peel the grid side of the backing off exposing the adhesive side and apply to surface.
4. Do a visual check to be sure your decal has adhered to the surface. If there are any air bubbles, CAREFULLY push the air out with your finger or very lightly with a squeegee (or CC). However, most bubbles will disappear in a few weeks due to the heat from the sunlight.

****If you have any questions, please email us at: Email: Sales@UtmostPromotions.com***

Removal options include:

- *Gently lift a corner of the decal and remove slowly at a 90 degree angle to the glass to avoid stretching the material. The decal can then be carefully placed back on the original backing sheet adhesive side down and stored.*